



NESTE PAINE ZFX

Industrial Hydraulic Oil

ISO VG 32

ISO VG 46

ISO VG 68

Neste Paine ZFX is ashless high quality hydraulic oil for industrial applications. It has excellent wear protection and filterability properties. It meets the new Denison HF-0 specification which is based on severe Denison T6H20C hybrid pump test. Good filterability and protection of yellow metals are the key factors in the test. New environmentally friendly additives contain no metals.

TYPICAL CHARACTERISTICS	32	46	68	100
Densitykg/m ³ 15°C	872	876	881	885
Flash Point°C (COC)	208	220	240	252
Pour Point°C	-27	-27	-24	-18
Viscosity Index	101	104	103	98
ViscositycSt/ 40 °C	32	46	68	100
ViscositycSt/ 100 °C	5,3	6,8	8,9	11,3
FZG	11	12	12	12

Applications for Neste Paine ZFX are different kind of industrial hydraulic systems. Neste Paine ZFX is the right choice when a high performance environmentally friendly industrial hydraulic oil is required.

DIN 51524 part 2, HLP

ISO 11158 HH, HL, HM

Denison HF-0, HF-1, HF-2

Vickers (Eaton) I-286-S

Vickers (Eaton) M-2950-S

General Motors LS-2

Cincinnati Machine P-68, P-69, P-70

Bosch Rexroth RE 90 220

Neste Markkinointi Oy

PL 95, 00095 NESTE OIL

www.neste.fi

Technical service

+358 200 11311

Updated 19.2.2007

Print

Close