



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150

Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491

Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE PDO Light

*NSF International H-1 & 3H Registered
"This product is certified OU Kosher Pareve"
"This product is Halal Certified"

LUBRIPLATE PDO Light meets U. S. FDA Regulation 21 CFR 172.878 for direct contact with food. It is recommended for pan divider oil applications.

Typical Properties:

Viscosity, ASTM D445, cSt @ 40°C	6.7 - 10.5
Viscosity, ASTM D445, cSt @ 100°C	2.45
Viscosity Index, ASTM D2270	83
Gravity, ASTM D4052, °API	33.7
Specific Gravity @ 25°C, ASTM D4052	0.827 - 0.846
Color, Saybolt, ASTM D156	30 Min.
Flash Point	350°F
Pour Point	-24°C/-11°F
Density	6.89 lbs/Gal

Packaging Available

5-Gallon Pail
55-Gallon Drum

Part No.

L0853-060
L0853-062

***NSF International H-1 & 3H Registration No.**

(*NSF International)

142304

This product meets the requirements as per 21 CFR 172.878 and 21 CFR 178.3620(a).

Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

Registered 3H by NSF International - These products are acceptable for use as Release Agents (3H) on grills, ovens, loaf pans, boning benches, chopping boards or other hard surfaces in contact with meat and poultry food products to prevent food from adhering during processing.

"The **LUBRIPLATE PDO Light** contain no components derived from TSE/BSE relevant animal species, therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".