

PLANTOSYN 32 HVI, 46 HVI, 68 HVI

Environmentally acceptable hydraulic fluid and lubricating oil based on saturated synthetic esters

Description

The PLANTOSYN HVI oils are environmentally acceptable high-performance hydraulic and lubricating oils based on saturated synthetic esters. These oils can be used universally in all hydraulic systems, even under severe operating conditions. PLANTOSYN 46 HVI has been tested and approved by well-known manufacturers of hydraulic components like Bosch Rexroth and Sauer Sundstrand. PLANTOSYN HVI products fulfill and surpass the requirements according to ISO 15380. PLANTOSYN HVI products are normally compatible with materials usually found in hydraulic systems. For dynamic stress as seals the use of viton FKM material is recommended.

Application

PLANTOSYN HVI oils are rapidly biodegradable synthetic saturated ester oils. They can be used in all applications in mobile and stationary hydraulic units where the use of biodegradable synthetic ester based hydraulic oil according to ISO 15380 HEES is recommended. The PLANTOSYN HVI products should be used where oil leakage or oil spillage will give a soil or water pollution. PLANTOSYN HVI products can be used as an alternative to conventional HLP/HM hydraulic oils. The changing over procedures according ISO 15380 have to be observed.

Specifications/Approvals

The products of the PLANTOSYN HVI series fulfill and surpass the requirements of:

- ISO 15380: HEES (saturated esters)

Advantages

- Based on renewable resources
- Rapidly biodegradable (> 60 % acc. to OECD 301 B)
- Multi-purpose characteristic (multi grade)
- Miscible with mineral oil and polyalphaolefin
- Excellent viscosity temperature behaviour (high VI)
- Good low temperature behaviour
- Shear stable
- Good corrosion protection
- Natural dissolving properties
- Very high resistance to ageing
- Excellent hydrolytic stability
- Very good wear protection
- Excellent lubricating properties
- Lifetime lubricating possible



EU Ecolabel: PLANTOSYN 32 HVI: DE/027/104
PLANTOSYN 46 HVI: DE/027/105
PLANTOSYN 68 HVI: DE/027/106



Better for the environment...

- geringfügige Schädigung von Wasser und Boden bei der Anwendung
- enthält einen großen Anteil von Ausgangsstoffen auf biologischer Basis
- reduced harm for water and soil during use
- contains a large fraction of biobased material

better for you.

PLANTOSYN 32 HVI, 46 HVI, 68 HVI

Environmentally acceptable hydraulic fluid and lubricating oil based on saturated synthetic esters

Typical technical data:

PLANTOSYN					
Product name		32 HVI	46 HVI	68 HVI	
Properties	Uni				Test method
Density at 15 °C	kg/m ³	0.915	0.913	0.916	ISO 12 185 , ISO 3675
Colour		0.5	0.5	0.5	ISO 2049
Appearance at 25 °C		clear, bright	clear, bright	clear, bright	
Ash content	% (m/m)	0	0	0	ISO 6245
Flashpoint in open cup acc. to Cleveland	°C	220	280	280	ISO 2592
Kinematic viscosity					ISO 3104
at - 20 °C	mm ² /s	1450	2670	4820	
at 0 °C.	mm ² /s	270	440	750	
at 40 °C	mm ² /s	32	46	68	
at 100 °C	mm ² /s	6.23	8.2	10.55	
Pourpoint	°C	- 46	- 36	- 27	ISO 3016
Low temperature fluidity after 7 days	°C	stable	stable	stable	ASTM D 2532
Acid number	mg KOH/g	0.55	0.55	0.55	ISO 6618
Water content	mg/kg	< 500	< 500	< 500	ISO 12 937, ISO 6296
copper corrosion (3 h, 100 °C)	degree of corrosion	1	1	1	ISO 2160
Rust prevention procedure A	degree of corrosion	0 - A	0 - A	0 - A	ISO 7120
Foaming					ISO 6247
Seq. I, at 24 °C	ml	0/0	0/0	0/0	
Seq. II, at 93 °C	ml	0/0	0/0	10/0	
Seq. III, at 24 °C	ml	0/0	0/0	0/0	
Air release at 50 °C	min	3	7	9	ISO 9120
Water separation time to 3 ml emulsion at 54 °C	min	10	25	25	ISO 6614

PI 4-1273 , Page 2 ; PM 4 / 08.13

PLANTOSYN 32 HVI, 46 HVI, 68 HVI

Environmentally acceptable hydraulic fluid and lubricating oil based on saturated synthetic esters

Typical technical data (continued):

PLANTOSYN					
Product name		32 HVI	46 HVI	68 HVI	
Properties	Unit	Test temperature at			Test method
Elastomer compatibility after 1.000 h		80 °C	80 °C	100 °C	ISO 6072
Change in hardness NBR 1		- 5.3	6.7	- 4.8	
Change in volume NBR 1	%	12.4	11.2	9.9	
Change in elongation NBR 1	%	- 8	- 10.4	- 25.6	
Change in tensile strength NBR 1	%	- 15.9	- 7.7	- 29.2	
Change in hardness HNBR1		- 5.7	- 4.9	- 4.2	
Change in volume HNBR1	%	11.8	9.7	8.3	
Change in elongation HNBR1	%	- 9.6	- 8.9	- 15.6	
Change in tensile strength HNBR1	%	- 7	- 5.8	- 21.3	
Change in hardness FPM AK 6		- 1.2	- 1.1	- 0.9	
Change in volume FPM AK 6	%	1.2	1	0.9	
Change in elongation FPM AK 6	%	- 7.5	- 8.2	- 6.5	
Change in tensile strength FPM AK 6	%	9	8	7.5	
Change in hardness AU		0.5	0.4	0.2	
Change in volume AU	%	- 0.6	- 0.5	- 0.3	
Change in elongation AU	%	- 8.1	- 7.9	- 5.3	
Change in tensile strength AU	%	- 4.3	- 5.2	- 3.6	
Oxidation stability					ASTM D 943
Modified TOST test, dry TOST					without water
time to reach Delta TAN					
2.0 mg KOH/g	h	> 4000	> 2000	> 2000	
Baader test, 110 °C, 72 h					DIN 51 554-3
increase in viscosity at 40 °C	%	< 1	< 1	< 1	
Load carrying properties	failure	11	12	12	ISO 14 635-1,
FZG A/8.3/90	load stage				DIN 51 354-2
Vane pump (Vickers V105C)					ISO 20 763
- weight loss ring	mg	13	< 120	< 120	DIN 51 389-2
- weight loss vanes	mg	10	< 30	< 30	



PLANTOSYN 32 HVI, 46 HVI, 68 HVI

Environmentally acceptable hydraulic fluid and lubricating oil based on saturated synthetic esters

The information contained in this product information is based on the experience and know-how of FUCHS EUROPE SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS EUROPE SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS EUROPE SCHMIERSTOFFE GMBH.

© FUCHS EUROPE SCHMIERSTOFFE GMBH. All rights reserved.