

## Granville Platinum 10W/40

1 Litre, 5 Litre, 25 Litre & 199 Litre

### Product Description

Granville Platinum 10W/40 is a high performance semi synthetic oil suitable for petrol and diesel engines including turbo, fuel injection and catalytic converters.

### Recommended for use by Granville for the following manufacturer's specifications

ACEA A3/B3  
ACEA E2  
API SL/CF  
MB 229.1  
VW 502.00  
VW 505.00



\* Image for illustrative purposes only.

### Product Benefits

- \* Ensures lubricant performance
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### Product Usage

For engines where this specification lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Keep sealed in a cool, dry place.

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Specific Gravity	:	0.878 @ 15.6°C (typical)
Solubility	:	Insoluble in water
Flashpoint	:	>200°C
Kinematic Viscosity @ 40°C	:	92.41 cSt (typical)
Kinematic Viscosity @ 100°C	:	13.7 cSt (typical)

Size	Part No	Barcode
1 Litre	0045	5020618000457
5 Litre	0043	5020618000433
25 Litre	0033	5020618000334
199 Litre	0034	5020618000341



# TECHNICAL

Data

## Granville Platinum 10W/40

1 Litre, 5 Litre, 25 Litre & 199 Litre



### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

*\* The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 1 | Date: 16/03/2012

