

# POWERWAY GE LA 15W-40

Gas engine oil for vehicles (CNG).

## Product description

POWERWAY GE LA 15W-40 is an engine oil for gas-powered vehicle engines.

## Application areas

POWERWAY GE LA 15W-40 is primarily intended for vehicle gas engines, normally in urban traffic. Examples of such vehicles are gas-powered inner city buses, refuse-collection trucks and other distribution vehicles.

## Characteristics and advantages

Good oxidation stability, even at high operating temperatures, facilitating an extended oil lifetime. Technology for wear protection and corrosion protection provides a long component lifetime.

## Tests and approvals

Specifications: API CF

Approvals: Cummins CES 20074

## Handling and storage

For additional information, see Safety Data Sheet

## Typical Data

Characteristics	Typical value	Unit	Method
CCS at -20°C	5830	mPas	ASTM D 5293
Density at 15°C	879	kg/m <sup>3</sup>	ISO 12185
Flash point COC	222	°C	ISO 2592
HT/HS	4.2	mPas	CEC L-36-A-90
Pour point	-24	°C	ISO 3016
TBN	5.2	mg KOH/g	ASTM D 2896
Viscosity at 40°C	97	mm <sup>2</sup> /s	ISO 3104
Viscosity at 100°C	13.1	mm <sup>2</sup> /s	ISO 3104
Viscosity index	134	-	ISO 2909

Revision date 01-Sep-2015