Product data sheet



POWERWAY 10W

Monograde engineoil for dieselengines.

Product description

POWERWAY 10W is a mineral oil-based monograde engine oil.

Application areas

POWERWAY 10W is recommended for diesel engines with or without turbo, hydraulic systems and transmissions where a monograde SAE 10W engine oil is prescribed.

Characteristics and advantages

Provides excellent protection where monograde oils are prescribed. Contains additives that help counteract wear, corrosion and oxidation. Formula that keeps the engine free of deposits and combustion residues. Extends engine life and minimises the risk of lubricant-related downtime. Good for use in various applications such as hydraulic systems, transmissions, compressors and converters where an SAE 10W engine oil is required.

Tests and approvals

Specifications: API SG, API CD

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.statoillubricants.com or supplied on request.

Typical Data

Characteristics	Typical value	Unit	Method
CCS at -25°C Density at 15°C Flash point COC Pour point TBN Viscosity at 40°C Viscosity at 100°C	5830 878 220 -36 6 39 6.7	mPas kg/m³ °C °C mg KOH/g mm²/s mm²/s	ASTM D 5293 ISO 12185 ISO 2592 ISO 3016 ASTM D 2896 ISO 3104 ISO 3104
Viscosity index	127	-	ISO 2909