

POWERWAY 15W-40

Engine oil for all types of diesel engines

Product description

POWERWAY 15W-40 is a multigrade diesel engine oil approved by leading engine manufacturers.

Application areas

POWERWAY 15W-40 is designed for vehicles in heavy traffic and construction, forestry and agricultural machines, both with and without turbo. POWERWAY 15W-40 is also suitable for passenger cars as well as light trucks and distribution vehicles. Can be used to advantage as a universal oil for a mixed fleet of machines and vehicles. Provides good engine protection under most operating conditions.

Characteristics and advantages

Universal oil that suits most petrol and diesel engines, reducing the need for several oils for different vehicles. Provides reliable protection and is suitable for most turbo engines. Contains additives that help counteract pollutants, wear and corrosion. Ensures piston cleanliness and long engine life. Delivers easy starting and good lubrication at low temperatures. Excellent lubrication under most operating conditions.

Tests and approvals

Specifications: ACEA E2, API CF, API SG, API SH

Fulfills: MB-Approval 228.1, MAN M 271

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.statoillubricants.com or supplied on request.

Typical Data

| Characteristics | Typical value | Unit | Method |
|--------------------|---------------|--------------------|---------------|
| CCS at -20°C | 6140 | mPas | ASTM D 5293 |
| Density at 15°C | 878 | kg/m ³ | ISO 12185 |
| Flash point COC | 220 | °C | ISO 2592 |
| HT/HS | 3.99 | mPas | CEC L-36-A-90 |
| Pour point | -36 | °C | ISO 3016 |
| TBN | 7.0 | mg KOH/g | ASTM D 2896 |
| Viscosity at 40°C | 103 | mm ² /s | ISO 3104 |
| Viscosity at 100°C | 14.2 | mm ² /s | ISO 3104 |
| Viscosity index | 140 | - | ISO 2909 |

Revision date 03-Sep-2015