

# POWERWAY 30

Monograde engineoil for dieselengines.

## Product description

POWERWAY 30 is a mineral oil-based monograde engine oil.

## Application areas

POWERWAY 30 is recommended for diesel engines with or without turbo, hydraulic systems and transmissions where a monograde SAE 30 engine oil is prescribed.

## Characteristics and advantages

Provides excellent protection where monograde oils are prescribed. Contains additives that help counteract wear, corrosion and oxidation. Formula that keeps the engine free of deposits and combustion residues. Extends engine life and minimises the risk of lubricant-related downtime. Good for use in various applications such as hydraulic systems, transmissions, compressors and converters.

## Tests and approvals

Specifications: ACEA E2, API CF-2, API CF/SG

Approvals: MTU Type 2

Fulfills: ZF TE-ML 04B, ZF TE-ML 02H, Allison C-4, MB-Approval 228.0, MAN M 271

## Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on [www.statoillubricants.com](http://www.statoillubricants.com) or supplied on request.

## Typical Data

Characteristics	Typical value	Unit	Method
CCS at -10°C	2900	mPas	ASTM D 5293
CCS at -15°C	5710	mPas	ASTM D 5293
Density at 15°C	890	kg/m <sup>3</sup>	ISO 12185
Flash point COC	236	°C	ISO 2592
Pour point	-36	°C	ISO 3016
TBN	10.5	mg KOH/g	ASTM D 2896
Viscosity at 40°C	87	mm <sup>2</sup> /s	ISO 3104
Viscosity at 100°C	11.2	mm <sup>2</sup> /s	ISO 3104
Viscosity index	116	-	ISO 2909

Revision date 25-May-2015