

# NESTE OIL

---

## NESTE PREMIUM

Semi-synthetic engine oil

SAE 5W-40

API SL/CF

ACEA A3/B4

SAE 10W-40

API SJ/CF

ACEA A3/B3

Neste Premium is semi-synthetic engine oil for passenger car gasoline and diesel engines. Thanks to its semi-synthetic structure, the cold operation properties of Neste Premium oil are very good, and lubrication starts right away. Engine wear is prevented and fuel consumption reduced. Since the synthetic base oil has a lower evaporative tendency than mineral oil, it guarantees a durable lubrication film in hot operating conditions and keeps oil consumption low.

Neste Premium contains the best modern additives, intensifying lubrication power, preventing deposit and corrosion formation and keeps it's stability through oil-change intervals.

TYPICAL CHARACTERISTICS	5W-40	10W-40
Densitykg/m <sup>3</sup> 15°C	855	872
Flash Point°C (COC)	220	222
Pour Point°C	-45	-39
Viscosity Index	169	155
ViscositycSt/ 40 °C	85	94
ViscositycSt/ 100 °C	13,9	14,2
ViscositycP/ °C	6000	6200

Neste Premium oil is recommended for year-round use in passenger car gasoline and diesel engines. It helps to guarantee reliable engine operation and the easy start-up, low oil consumption and engine cleanness.

Neste Premium oil can also be used in older engines.

Neste Markkinointi Oy  
PL 95, 00095 NESTE OIL  
www.neste.fi

Technical service  
+358 200 11311  
Updated 6.3.2014

Print

Close