



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

Sales, Service & Distribution Center  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support  
Phone: 1-800-733-4755

5 - 23A

## **LUBRIPLATE "Semi-Synthetic" Refrigeration Compressor Oil 68-P**

**LUBRIPLATE Refrigeration Compressor Oil 68-P** is a "semi-synthetic" highly refined, wax-free, paraffinic lubricant formulated for use in refrigeration compressor systems utilizing ammonia. It contains additives for oxidation inhibition, corrosion protection, pour point depression and defoaming.

**LUBRIPLATE Refrigeration Compressor Oil 68-P** is recommended for CFC (chlorofluorocarbon) and HCFC (hydro chlorofluorocarbon) refrigerants such as R-717, R-11, R-12, R-13, R-113, R-114, R-115, R-22, R-123, R-141b, R-500, R-501 and R-502. It is not recommended for use with HFC (hydrofluorocarbon) refrigerants such as HFC-134a. HFC's are more commonly recognized as freons.

### **Benefits**

- Extended Drain Intervals
- Excellent Chemical and Thermal Stability
- Minimizes Formation of Harmful Varnish, Gum and Sludge Deposits
- High Viscosity Index
- Low Pour Point
- Meets Frick No. 3 Oil Specifications

### **Typical Tests**

Viscosity Data	
cSt @ 40°C	62.9
cSt @ 100°C	8.5
SUS@ 100°F	351
SUS @ 210°F	54
Pour Point °F/°C	-38°F/-39°C
Flash Point °F/°C	468°F/242°C
Fire Point °F/°C	510°F/266°C
Floc Point °F/°C	-45°F/-43°C
Viscosity Index (VI)	106
Dielectric Strength	35 kv
Aniline Point °F/°C	247°F/119°C

### **Packaging Available**

5 Gallon Pail  
55 Gallon Drum

### **Part No.**

L0843-060  
L0843-062