

ROCKWAY EP 15

Pneumatic tool oil

Product description

ROCKWAY EP 15 is a pneumatic tool oil of very high quality. The product is made of solvent-refined paraffin base oil and special additives, which counteract wear and corrosion and produce good adhesion.

Application areas

ROCKWAY EP 15 can be used for all types of percussive pneumatic machines. It is used both within industrial applications as well as the building and construction sector, and within mining and quarrying.

Characteristics and advantages

ROCKWAY EP 15 is made of solvent-refined paraffin base oil and special additives, which counteract wear and corrosion and produce good adhesion. For working environment reasons, the oil has been formulated to produce the least possible oil mist. The product's high viscosity index ensures good lubrication at both high and low temperatures. The properties of ROCKWAY EP 15 reduce wear and maintenance costs, as well as contributing to a longer component lifetime.

Tests and approvals

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.statoillubricants.com or supplied on request.

Typical Data

| Characteristics | Typical value | Unit | Method |
|--------------------|---------------|--------------------|-----------|
| 4-ball, WL | 276 | kg | ISO 20623 |
| Density at 15°C | 894 | kg/m ³ | ISO 12185 |
| Flash point COC | 147 | °C | ISO 2592 |
| Pour point | -57 | °C | ISO 3016 |
| Viscosity at 40°C | 16.6 | mm ² /s | ISO 3104 |
| Viscosity at 100°C | 3.7 | mm ² /s | ISO 3104 |
| Viscosity index | 114 | - | ISO 2909 |

Revision date 12-Jan-2015