CITGO

CITGO RUST-O-LENE® LT

Date 10/12

DESCRIPTION:

CITGO Rust-O-Lene LT is a rust preventative oil formulated with effective rust inhibitors and high quality base oils. It exhibits excellent metal wetting and water displacement properties and is designed for temporary protection of metal parts during manufacturing and storage. CITGO Rust-O-Lene LT can also be used as a hydraulic and circulating oil where added rust protection is required.

FEATURES:

- · May be applied by dipping, spraying or brushing
- · Excellent water displacement properties
- · Excellent metal wetting
- Multi-purpose fluid

BENEFITS:

- Effective application on any part configuration
- · Protects parts after machining with aqueous cutting fluids
- Provides a high degree of prevention of fingerprint or perspiration acid corrosion
- Can be used as an hydraulic and circulating oil where robust corrosion protection is needed



CITGO Rust-O-Lene LT is used for longer term rust protection of semifinished or finished metal parts and assemblies that require longer term protection. It can be used by hydraulic and circulating systems for industrial equipment requiring better protection from rust.



Material Compatibility

| | Recommended | Highly Recommended |
|---------------------|-------------|--------------------|
| P - Steels | | |
| M - Stainless Steel | | |
| K - Cast Iron | | |
| N - Non-ferrous | | |
| | | |



Protected Metal

Unprotected Metal

TYPICAL PROPERTIES - CITGO RUST-O-LENE® LT

| Material Code | 639460001 |
|---|-----------|
| Gravity, ASTM D 4052, °API | 30 |
| Solvent Present | No |
| Flash Point, COC, ASTM D92, °F (°C) | 385 (196) |
| Viscosity, ASTM D 445, cSt at 40°C | 52 |
| ASTM D 2161, SUS at 100°F | 241 |
| Rust Protection, Humidity Cabinet (hours) | 1300 |