



Product Information

SCOOTER 4

SCOOTER FOUR STROKE ENGINE OIL

Description

Scooter 4 is an advanced SAE 10W-40 semi-synthetic engine lubricant developed from racing technology. It is recommended for all high performance 4-stroke scooter engines. High viscosity Index and excellent shear stability give genuine stay-in-grade performance, even in high revving engines, while excellent anti-wear performance ensures optimum reliability of both engine and gearbox components. Scooter 4 promotes outstanding cleanliness for efficient engine operation.

Applications

Scooter 4 is recommended for all four stroke scooter engines or two stroke gearboxes where the manufacturer specifies a product of this grade and type.

Performance Levels

API SL
JASO MA

Physical Characteristics

| | |
|------------------------------------|--------|
| SAE Classification | 10W-40 |
| Density at 15 °C | 0.87 |
| Kinematic Viscosity at 100 °C, cSt | 14.5 |
| Kinematic Viscosity at 40 °C, cSt | 94 |
| Viscosity Index | 150 |
| Flash Point (Closed) °C | 190 |
| TBN, mg/KOH/g | 10 |
| Sulphated Ash %Wt. | 1.2 |
| Pour Point, °C | -40 |

(TDS Scooter 4 – 020712 Issue 3)



Certificate No. FM 21756



Certificate No. EMS 60044



Certificate No. OHS 555083

Morris Lubricants, Castle Foregate,
Shrewsbury, Shropshire, SY1 2EL
Telephone (01743) 232200
Fax (01743) 353584