



Product Information

SERVOL PERFORMANCE PLUS 15W-40

Description

Servol Performance Plus 15W-40 is manufactured from high quality mineral oils and a high performance additive system. This grade is designed for use in petrol and diesel engines and their turbocharged versions.

Servol Performance Plus 15W-40 provides a good level of engine cleanliness and controls the formation of high temperature lacquers and low temperature sludges. Anti-wear technology ensures maximum component life, together with protection from oxidation, rust and corrosion.

Applications

Typical applications for Servol Performance Plus 15W-40 include pre-2004 passenger cars and vans (where manufacturers specify ACEA A3/B4 in handbooks) and commercial vehicles (Euro 1 and Euro 2 compliant), where the following would have been originally stated: MB 228.1, MAN 271, Mack EO-L, Volvo VDS and VW 505.00.

Note: This product must never be used in engines incorporating after-treatment devices. This includes: exhaust gas recirculation (EGR), diesel particulate filters (DPFs) and adblue systems.

Performance Levels

API CG-4 / CF-4 / SJ / SL

Physical Characteristics

Density at 15 °C	0.880
Kinematic Viscosity at 100 °C, cSt.	14.1
Kinematic Viscosity at 40 °C, cSt.	99
Viscosity Index	135
Flash Point (Closed) °C	200
Sulphated Ash, %Wt.	1.3
Pour Point, °C	-30
TBN, mg/KOH/g	11.0

(TDS Servol Performance Plus 15W-40 - 150912 Issue 15)



Certificate No. FM 21756



Certificate No. EMS 60044



Certificate No. OHS 555083

Morris Lubricants, Castle Foregate,
Shrewsbury, Shropshire, SY1 2EL

Telephone (01743) 232200

Fax (01743) 353584