

## Product Information

# SERVOL SEMI-SYNTHETIC 10W-40

---

## Description

Servol 10W-40 is manufactured from high quality base fluids and a carefully balanced additive system. This grade is suitable for use in petrol and diesel engines fitted to passenger cars and light commercial vehicles. Servol 10W-40 provides a good level of engine cleanliness and will protect critical components, such as camshafts, valve gear and bearings from wear as well as ensuring overall protection from rust and corrosion.

## Applications

Servol 10W-40 is suitable for use in passenger cars, light commercial vehicles, horticultural equipment, etc., where a grade of this type and performance level is required.

## Performance Levels

API SL / SJ / CF  
ACEA A3 / B4

## Physical Characteristics

Density at 15 °C	0.877
Kinematic Viscosity at 100 °C, cSt.	14.25
Kinematic Viscosity at 40 °C, cSt.	95.0
Viscosity Index	150
Flash Point (Closed) °C	200
Sulphated Ash, %Wt.	0.9
Pour Point, °C	-35

(TDS Servol 10W-40 – 191214 Issue 15)



Certificate No. FM 21756



Certificate No. EMS 60044



Certificate No. OHS 555083

Morris Lubricants, Castle Foregate,  
Shrewsbury, Shropshire, SY1 2EL  
Telephone (01743) 232200  
Fax (01743) 353584