

NESTE OIL

NESTE SPECIAL

Single and multigrade engine oils

API SF/CC (SAE 10W-30)

API SG/CF-4 (SAE 20W-50)

API SG/CF-4 (SAE 30 and 40)

Neste Special is a series of solvent-refined engine oils made of selected paraffinic base oils. Tested additives make it a top quality engine oil for normal use. In addition to its good lubrication power, it protects against wear, sedimentation, deposit formation and corrosion.

TYPICAL CHARACTERISTICS	30	40	10W-30	20W-50
Densitykg/m ³ 15°C	885	899	852	887
Flash Point°C (COC)	230	260	240	270
Pour Point°C	-27	-27	-36	-21
Viscosity Index	105	115	144	131
ViscositycSt/ 40 °C	95	128	64	178
ViscositycSt/ 100 °C	11,3	14,6	10,1	18,2
ViscositycP/ °C			5000	7100
Sulfated ash w-%		0,66		

Neste Special oils are recommended for most gasoline engines. They can also be used successfully in diesel engines that are not turbocharged. Neste Special 10W-30 is suitable for normal year-round use.

Neste Special 20W-50 is a more viscous grade with a good high temperature resistance that keeps oil consumption down. Especially suitable for summer use.

Neste Special 30 and 40 are suitable transmission oils also in cases which a single-grade 'straight' quality is recommended. They are in line with API GL-1.

Neste Markkinointi Oy
PL 95, 00095 NESTE OIL
www.neste.fi

Technical service
+358 200 11311
Updated 28.3.2013

[Print](#)[Close](#)