

Product Information

SPORT ACTION 2

MOTORCYCLE TWO STROKE ENGINE OIL

Description

Sport Action 2 is a race developed two stroke lubricant incorporating fluid technology developed from experience gained in motorcycle racing. This grade is synthetic and provides maximum film strength and anti-wear characteristics, even under shock load conditions that can be experienced in competition use. The lubricating film is strong enough to prevent engine lock up in moments of temporary overheating. Sport Action 2 uses advanced anti-wear chemistry to protect all the critical components of the engine, including main and big end bearings, gudgeon pins, rings and bores. Sport Action 2 burns extremely cleanly and not only produces minimal white smoke, but virtually eliminates deposits on spark plugs, even if an over-rich mixture has been inadvertently used.

Applications

Sport Action 2 has been formulated for use in two stroke engines and maybe used as a pre-mix or in oil injection systems. Recommended for motorcycles used in the competition arena, including circuit racing, road racing and off-road.

Performance Levels

JASO FC

API TC

Physical Characteristics

Grade

Colour	Red
Density at 15 °C	0.880
Kinematic Viscosity at 100 °C, cSt	9.5
Kinematic Viscosity at 40 °C, cSt	56
Viscosity Index	145
Pour Point, °C	-40
Flash Point (Closed) °C	85

SDS: 7512, Issue: 1, Ref: 512.450



Certificate No. FM 21756
BS EN ISO9001 2000

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire SY1 2EL

Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044
BS EN ISO14001 1996