



### LEVELS OF QUALITY

The lubricant STS PLUS MIX 2T complies with the following international specifications:

- API TC
- JASO FC

### DESCRIPTION

The lubricant Douglas STS PLUS MIX 2T can be used in motorcycle and scooter engines with automatic or separate blending.

Furthermore it can be used in two-stroke engines installed on agricultural machineries and in two-stroke engines of mowers and motor saws.

The special additives used offer a good scratch protection of pistons, an effective anti-wear action and a good protection against spark plug clogs.

### APPLICATIONS

Its specific formulation ensures a perfect lubricant leakage inside lead-free petrol engines, by improving the combustion and the efficiency of the engine.

The following benefits can be obtained, if you use this product:

- reduction in smokes coming from the exhaust pipe;
- a higher engine cleaning.

### TYPICAL FEATURES

Density at 15°C.Kg./dm <sup>3</sup>	ASTM D1298	0.860
Viscosity at 100°C.cSt	ASTM D445	11.0
Colour	visual	red
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-9

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

