



NESTE SUOJAÖLJY LO

Corrosion protective

Neste Suojaöljy LO is made of thin oil mixed with effective anti-corrosives. It contains no solvent and poses no fire risk. It is light in colour and spreads easily on the surfaces to be protected. Neste Suojaöljy LO gives good resistance against pit corrosion. It also conducts electricity.

TYPICAL CHARACTERISTICS

Densitykg/m ³ 15°C	876
Flash Point°C (COC)	228
Pour Point°C	-36
Viscosity Index	111
ViscositycSt/ 40 °C	35
ViscositycSt/ 100 °C	5,9
Colour D 1500	L3.0

Neste Suojaöljy LO is recommended for protecting steel plates and parts if solvent-diluted antirust agents cannot be used because of the fire risk.

Neste Suojaöljy LO has been designed to meet the requirements of the steel industry, particularly in the case of steel surfaces stored outdoors under cover. It is also suitable for protecting aluminium. Coverage c. 30 m²/litre.

Neste Suojaöljy LO can be applied by spraying, immersing or brushing, and can be removed by washing with solvent. It burns on tempering, without leaving marks on polished metal surfaces.

Neste Markkinointi Oy
PL 95, 00095 NESTE OIL
www.neste.fi

Technical service
+358 200 11311
Updated 3.12.2001

[Print](#)[Close](#)