

Klüber Summit Varnasolv

Concentrated, synthetic conditioner for compressors, hydraulic systems, gears and other oil circulation systems



Benefits for your application

- Dissolves varnish and carbon deposits, thus reducing maintenance and cleaning costs – no dismantling of systems needed prior to cleaning
- Used during operation, no downtime of machines for cleaning
- Easy application due to the neutral behaviour towards seals, when added to the compressor oil on 1 to 10 basis
- Reduced operating and maintenance costs due to higher efficiency (e.g. compressor) and longer service life of the fresh oil fill

Description

Klüber Summit Varnasolv is a concentrated conditioner fluid containing synthetic ester oil and cleaning additives. It is miscible with mineral oils, synthetic hydrocarbons, ester oils and polyglycols.

Application

Klüber Summit Varnasolv has been especially designed for cleaning screw-type compressors, hydraulic systems, gears and other oil circulating systems like calendars. The conditioner can be used for oils based on mineral oil, synthetic hydrocarbon, ester oil and polyglycol.

Using mineral oils in oil-injected screw-type and sliding vane compressors may lead to varnish and carbon buildup in the entire oil circuit or form sticky residues on valves and hot surfaces in hydraulic systems. This often results in increased energy consumption, sticky valves, clogged oil lines and filters and increased downtime due to maintenance.

Klüber Summit Varnasolv is a concentrated conditioner fluid which dissolves varnish and carbon buildups during operation and keeps them suspended in the compressor oil. Therefore, it is no longer necessary to dismantle the system for cleaning. The oil containing the residues is completely drained before refilling the unit with fresh oil.

60 hours at an operating oil temperature of 70 – 80°C, if possible, to dissolve all varnish and carbon buildups or sticky residues. Drain the unit after max. 80 hours. Make sure the oil is also removed from tubes, filter housings and dead corners, because the used oil fill may severely affect the fresh oil. Then exchange filters and oil separators and refill the unit with the fresh oil.

Especially when using Klüber Summit Varnasolv in gears and other highly loaded units please take the viscosity and the wear protection of the oil/Varnasolv mixture into consideration when adding Varnasolv to the oil fill.

Your contact persons at Klüber Lubrication would be pleased to assist you in cleaning your machines with Klüber Summit Varnasolv.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Application notes

Add Klüber Summit Varnasolv to the oil fill on 1 to 10 basis. Be sure to drain enough compressor oil to allow for the additional quantity. Let the unit continue operating for an additional 40 to

Pack sizes	Klüber Summit Varnasolv
Canister 3.8 l	+
Canister 19 l	+
Drum 208 l	+



Klüber Summit Varnasolv

Concentrated, synthetic conditioner for compressors, hydraulic systems, gears and other oil circulation systems

Product data	Klüber Summit Varnasolv
Article number	050017
NSF-HX-2 registration	147 218
Colour space	yellow
Appearance	clear
Density, DIN 51757, 20 °C	approx. 0.97 g/cm ³
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 30 mm ² /s
Flash point, DIN EN ISO 2592, Cleveland, open-cup apparatus	>= 230 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.



a company of the Freudenberg Group