



## SUPER ATF DEXRON III SYNT

REV.1 OF MARCH /2013

### LEVELS OF QUALITY

The lubricant **SUPER ATF DEXRON III SYNT** complies with the following international specifications:

GM DEXRON III-IIIH-IIIE · MB 236.5-236.9-236.10-236.11-236.12 · VOITH G607 · ALLISON C-4 · CAT TO-2 · ZF TE-ML02F,03D,04D, 14B,16L,17C · MAN339 V2/Z2 · VOLVO 97341 · FORD MERCON V

### PRODUCT DESCRIPTION

DUGLAS OIL SUPER ATF DEXRON III SYNT is a fluid based on a synthetic technology which is produced using carefully selected and balanced components and recommended for automatic transmissions, power steering, hydraulically assisted steering and torque convertors, whenever it is required a product able to satisfy the requirements of GENERAL MOTORS Dexron III - IIIH - IIE.

It is especially recommended for hydraulic frictions to select the gears within the BMW and Mercedes Benz powershift.

### APPLICATIONS

It ensures excellent performances in terms of:

- frictional properties;
- thermal-oxidative stability;
- wear and corrosion resistance;
- foaming resistance;
- compatibility with components for automatic transmissions, elastomer seals and plastic parts;
- extending oil change intervals;
- fuel economy.

Thanks to the above mentioned features and to a high viscosity index it also ensures an excellent cold fluidity, by maintaining the desired viscosity at high temperatures.

### TYPICAL FEATURES\*

Density at 15°C.Kg./dm3	ASTM D1298	0.860
Colour		Amber
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	160
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-33

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

