

CEPSA SUPER EXTRA HD

Description

Lubricant especially recommended for petrol and diesel engines in fleets of public-service vehicles in highly severe operating conditions.

Applications

- Suitable for use in normally aspirated diesel engines, farm tractors, quarrying machinery and stationary engines.

Performance

- High detergent-dispersant capacity. Keeps vital engine parts clean.
- Great oxidation stability. High protection against the formation of deposits, sludge and lacquer at any temperature.
- Great corrosion protection. Prevents corrosion in cylinders and bores.
- High antifoam resistance. Reduces clogging in oil filters.

Specifications

• API SF/CF

• ALLISON C3

Typical Characteristics

CHARACTERISTICS	ASTM STANDARD (ISO-3448)	CEPSA SUPER EXTRA HD		
		10W	30	40
SAE Grade				
Density 15°C, g/cc	D-4052	0.880	0.895	0.898
Flash Point (COC) °C	D-92	>230	>230	>250
Pour Point, °C	D-97	-33	-15	-15
Viscosity at 100°C, cSt	D-445	6.15	11.9	14.5
Viscosity at 40°C, cSt	D-445	38	108.3	148
Viscosity Index	D-2270	108	98	96

Health & Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.