



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150

Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491

Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE Super HDS 40 Motor Oil

LUBRIPLATE Super HDS 40 Motor Oil is a high-quality diesel engine oil designed for use in a wide variety of applications, including off-highway diesel equipment, farm machinery, marine engines, 2-stroke cycle diesel engines (in the appropriate viscosity grades) and mixed commercial fleets. It may be also used in some heavy duty manual transmissions in trucks and busses.

Benefits:

- Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- Protects against sludge and varnish formation
- Protects against scuffing and wear
- Protects against rust and bearing corrosion
- Good resistance to foaming and aeration
- Low-ash content to minimize the formation of ash deposits and helps keep intake ports clean

Meets or exceeds the following specifications:

- API CF-2
- API CF (obsolete)
- Detroit Diesel 2-stroke cycle engines, Oil Type 1 (1.0 % max. Sulfated ash)
- Arvin Meritor, Dana Spicer and Eaton Fuller manual transmissions

(Over)

LUBRIPLATE Super HDS 40 Motor Oil:

Typical Tests

Viscosity, Kinematic	
cSt @ 40°C	149
cSt @ 100°C	15.4
SAE Grade	40
Viscosity Index	106
Pour Point, °F	-27
TBN (min)	8.1
Zinc, wt %	0.109
Sulfated Ash % wt	1.0

LUBRIPLATE Super HDS 40 Motor Oil is available in the following:

<u>Packaging Available</u>	<u>Part Numbers</u>
Carton, 12/1 Quart Plastic Bottles	L0792-054
5 Gallon Pail	L0792-060
55 Gallon Drum	L0792-062

Printed in USA
Revised 4-26-12