

ISO-9001 Registered Quality System. ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE Super HDS 5W-20 Motor Oil

LUBRIPLATE Super HDS 5W-20 Motor Oil is a superior-quality, high detergent automotive engine oil specially formulated with synthetic base stocks and mineral oil for better fuel economy and to reduce harmful emissions while meeting and exceeding the OEM's stringent lubrication requirements of today's engines. **LUBRIPLATE Super HDS 5W-20 Motor Oil** can be used in passenger cars, light trucks and sport utility vehicles under all operating conditions. **LUBRIPLATE Super HDS 5W-20 Motor Oil** is formulated using an advanced additive package that provides maximum protection against wear, rust, corrosion, thermal breakdown, acid formation, reduces sludge build up and the formation of sludge and varnish deposits.

Benefits

- Friction-modified for improved fuel economy
- Protects against sludge and varnish formation
- Helps protect emissions system
- Minimized rust and corrosion
- Good low temperature pour point
- Excellent resistance to viscosity and thermal breakdown at high temperatures

Meets or exceeds the following specifications:

- API Service Category SN, SM, SL, SJ, SH, SG, SF, SE, SD or SC
- Energy Conserving, ILSAC GF-5
- Meets or exceeds the requirements of MIL-1-46152E
- Ford WSS-M2C930-A
- DaimlerChrysler DC MS-639N, MS-6395L
- GM 6094M specification, GM9986202
- SAE 5W20 Meets Ford, Honda and Mazda service fill requirements

LUBRIPLATE Super HDS 5W-20 Motor Oil

Typical Tests

Viscosity, Kinematic	
cSt @ 100°C	8.7
6600 cP max @ Deg C	-35
SAE Grade	5W20
Viscosity Index	150
Specific Gravity	0.863
Flash Point, COC °F	400
Pour Point, °C (min)	-39

LUBRIPLATE Super HDS 5W-20 Motor Oil is available in the following packaging:

Packaging Available	Part Numbers
Case, 12/1 Quart Plastic Jugs	L0789-054
5 Gallon Pails	L0789-060
55 Gallon Drums	L0789-062

Printed in USA Revised 11/1/11