



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150

Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491

Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE Super Lo-Hi-Vis 20W-50 Motor Oil

LUBRIPLATE Super Lo-Hi-Vis 20W-50 Motor Oil is a high-quality, conventional engine oil designed for use in gasoline-fueled passenger cars and light trucks that do not require an ILSAC GF-5 oil for warranty coverage. **LUBRIPLATE Super Lo-Hi-Vis 20W-50 Motor Oil** also contains a boosted level of zinc dialkyldithiophosphate (ZDDP) additive to provide additional wear protection and enhanced oxidation resistance for use in the most demanding applications.

Benefits:

- Formulated for engines equipped with turbochargers or superchargers
- Excellent resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against rust and bearing corrosion
- Highly resistant to foaming
- High ZDDP content for additional wear protection for engines with flat-tappet camshafts (SAE 20W-50)

Meets or exceeds the following specifications:

- API Service SN

Typical Tests

SAE Grade	20W-50
Specific Gravity @ 60°F	0.879
Density, lbs/gal @ 60°F	7.32
Color, ASTM D1500	3.5
Flash Point COC, °C (°F)	230 (446)
Pour Point, °C (°F)	<-30 (<-22)

(Typical Tests Continued)

LUBRIPLATE Super Lo-Hi-Vis 20W-50 Motor Oil:

Typical Tests – Cont'd:

Viscosity, Kinematic	
cSt @ 40°C	155
cSt @ 100°C	18.6
Viscosity Index	134
Cold Cranking Viscosity, cP	7,000
@ (C)	(-15)
High-Temp/High-Shear Viscosity, cP @ 150°C	4.8
Sulfated Ash, ASTM D874, wt %	1.06
Total Base Number (TBN), ASTM D2896	8.6
Phosphorus, wt %	0.108
Titanium, wt %	0.010
Zinc, wt %	0.119

LUBRIPLATE Super Lo-Hi-Vis 20W-50 is available in the following:

Packaging Available

Part Numbers

Carton, 12/1-Quart Plastic Bottles	L0785-054
5 Gallon Pail	L0785-060
55 Gallon Drums	L0785-062