

Product Information

SUPER SPORT 2i

MOTORCYCLE TWO STROKE ENGINE OIL

Description

Super Sport 2i is a proven lubricant incorporating synthetic technologies developed from experience gained in motorcycle racing. This grade provides maximum film strength and anti-wear characteristics. The lubricating film is strong enough to prevent engine lock up in moments of temporary overheating. Super Sport 2i provides excellent wear protection for main and big end bearings, gudgeon pins, rings and bores, therefore extending component longevity. Deposit formation in ports and on spark plugs is virtually eliminated, even if an over-rich mixture has been inadvertently used.

Applications

Super Sport 2i is recommended for engines fitted with an oil injector system and has been specially formulated to maintain the correct lubricant metering viscosity in all conditions.

Performance Levels

JASO FC
API TC

Physical Characteristics

Grade

Colour	Red
Density at 15 °C	0.880
Kinematic Viscosity at 100 °C, cSt	9.5
Kinematic Viscosity at 40 °C, cSt	56
Viscosity Index	145
Pour Point, °C	-40
Flash Point (Closed) °C	85



Certificate No. FM 21756
BS EN ISO9001 2000

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire SY1 2EL

Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044
BS EN ISO14001 1996