



LEVELS OF QUALITY

The lubricant SUPER TTS SYNT complies with the following international specifications:

- API TC PLUS
- JASO FD
- ISO-L-EGD

DESCRIPTION

SUPER TTS SYNT is a synthetic blend oil which can be used in all 2-stroke motorcycle and scooter engines with automatic or separate blending.

Furthermore it can be used in two-stroke engines installed on agricultural machineries and in two-stroke engines of mowers and motor saws.

APPLICATIONS

Its specific SYNTHETIC formulation ensures a perfect lubricant dispersion inside lead-free petrol engines, by improving the combustion and the efficiency of the engine.

The following benefits can be obtained, if you use this product:

- reduction in smoke coming from the exhaust pipe;
- a higher engine cleaning.

TYPICAL FEATURES

Density at 15°C.Kg./dm3	ASTM D1298	0.905
Viscosity at 100°C.cSt	ASTM D445	9.0
Colour	visual	neutral
Flammability V.A. °C	ASTM D92	250
Pour Point °C	ASTM D97	-24

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

