# CITGO SUPERGARD® EUROPEAN FORMULA SAE 5W-40 MOTOR OIL



Date 03/15

#### **DESCRIPTION:**

CITGO SUPERGARD European Formula 5W-40 Motor Oil is a premium quality, high performance full synthetic oil formulated for use in certain European vehicles with gasoline engines. The specially crafted formulation contains a well-balanced combination of today's highest quality synthetic base stocks and an advanced additive system specifically designed to provide superior performance and protection under the most demanding driving conditions.

#### **QUALITIES:**

- Excellent low-temperature starting and pumpability characteristics
- · High-temperature/high-shear properties well above conventional oils
- · Extended drain interval capabilities
- · Lower volatility when compared to conventional oils
- · Excellent thermal and oxidation stability
- Enhanced protection against varnish buildup and sludge formation in critical engine parts for top performance and long engine life
- Extended engine life due to control of wear and deposit formation

#### **APPLICATIONS:**

- High performance full synthetic oil designed for use in certain Audi, BMW, Mercedes Benz, Volkswagen and other European vehicles with gasoline engines.
- Approved under VW Standard 502 00 and VW Standard 505 00
- · Formulated to meet referenced specifications for:
  - ► BMW Longlife-01
  - Mercedes Benz 229.5
  - API Service Category SN

NOTE: Product is pending BMW and Mercedes Benz approval.

## **TYPICAL PROPERTIES:**

## CITGO SUPERGARD® EUROPEAN FORMULA 5W-40 MOTOR OIL

SAE Grade	5W-40
Material Code	620884001
Gravity, ASTM D 4052, °API Pounds Per Gallon Flash Point, ASTM D 92, °F (°C), COC Low Temperature Cranking, ASTM D 5293	34.1 7.11 450 (232)
Temperature, °F (°C) Viscosity, cP Viscosity ASTM D 445, cSt at 40°C cSt at 100°C	-22 (-30) 5,935 82.6 13.6
Viscosity Index, ASTM D 2270 Pour Point, ASTM D 97, °F (°C) Color, ASTM D 1500 API SN	168 -51 (-46) L3.0 Yes
ILSAC GF-5	No