

CITGO SUPERGARD® ULTRALIFE®  
MOTOR OILS

Date 07/15

**DESCRIPTION:** CITGO SUPERGARD UltraLife Motor Oils are premium quality engine oils designed to improve the life of older higher mileage engines. They will provide optimum performance in these high-output gasoline (including turbocharged and supercharged) engines in passenger cars, vans, sport utility vehicles, and light trucks. These oils are formulated with highly refined base oils and additive systems that will handle those problems associated with the older, higher mileage engines that have exceeded their warranty. CITGO SUPERGARD UltraLife can be used in rebuilt and new engines.

**BENEFITS:** CITGO SUPERGARD UltraLife benefits your engine in the following ways:

- Provides extra wear protection
- Provides improved seal conditioning to help reduce oil leakage and valve deposits
- Offers excellent resistance to oil burn-off
- Provides extra cleaning to critical engine parts
- Helps improve overall engine performance
- Offers excellent oxidation and thermal stability to help maintain engine cleanliness and deposit formation
- Consult owner's manual for Fluid Specifications.

**APPLICATIONS:** CITGO SUPERGARD UltraLife Motor Oils are recommended for the older higher mileage, rebuilt, and new passenger cars, sport utility vehicles and light trucks operating on gasoline. CITGO SUPERGARD UltraLife Motor Oils are available in SAE 5W-30, 10W-30, and 10W-40 grades, are licensed for API SN, and are backward compatible with prior API Service Categories (SM, SL and SJ). Additionally, the SAE 5W-30 and SAE 10W-30 grades are licensed ILSAC GF-5 Resource Conserving.

**TYPICAL PROPERTIES:****CITGO SUPERGARD® ULTRALIFE® MOTOR OILS**

SAE Grade	5W-30	10W-30	10W-40
Material Code	620892001	620893001	620894001
Gravity, ASTM D 4052, °API	32.6	30.7	31.0
Density, lb/gal at 60°F	7.18	7.27	7.25
Flash point, COC, ASTM D 92, °F (°C)	450 (232)	450 (232)	453 (234)
Viscosity ASTM D 445, cSt at 40°C	65.7	73.5	102.0
cSt at 100°C	10.9	11.0	15.0
Viscosity Index	158	139	154
Pour Point, ASTM D 97, °F (°C)	-38 (-39)	-44 (-42)	-38 (-39)
Low Temperature Cranking at -22 °F (-30°C), ASTM D 5293, cP	6,250	—	—
Low Temperature Cranking at -13 °F (-25°C), ASTM D 5293, cP	—	6,180	6,080
Low Temperature Pumping at -31°F (-35°C), ASTM D 4684, cP	29,300	—	—
Low Temperature Pumping at -22°F (-30°C), ASTM D 4684, cP	—	23,200	31,500
Yield Stress, Pa	<35	<35	<35

CITGO, SUPERGARD and UltraLife are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.