

# Q8 T 630 DPF 5W-30

## Description

Ultra High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil for Euro 4, 5 and 6 engines for normal and extended drain intervals.

## Application

- For passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 4, 5 and 6 engines requiring LowSAPS engine oil.

## Specifications

- ACEA C3
- API SN/CF
- VW 502.00/505.01
- MB 229.51
- BMW Longlife-04
- ACEA C2 suitable for use

## Benefits

- LowSAPS formulation protecting Exhaust Catalyst and Diesel Particulate Filter.
- Excellent engine cleanliness and wear protection increasing engine durability.
- Reduces fuel consumption.
- Extended drain interval capability.

| Properties                  | Method | Unit               | Typical   |
|-----------------------------|--------|--------------------|-----------|
| Viscosity Grade             |        |                    | SAE 5W-30 |
| Absolute Density, 15 °C     | D 4052 | kg/m <sup>3</sup>  | 853       |
| Kinematic Viscosity, 100 °C | D 445  | mm <sup>2</sup> /s | 11.2      |
| Kinematic Viscosity, 40 °C  | D 445  | mm <sup>2</sup> /s | 66.5      |
| Viscosity Index             | D 2270 | -                  | 166       |
| Apparent Viscosity, -30 °C  | D 5293 | mPa.s              | 6300      |
| Sulphated Ash               | D 280  | % mass             | 0.8       |
| Pour Point                  | D 97   | °C                 | -36       |
| Flash Point                 | D 92   | °C                 | 210       |

*The figures above are not a specification. They are typical figures obtained within production tolerances.*