

DESCRIPTION

A new cylinder oil resulting from an optimized formulation which maintains the highest product performances for reliable operations and engine protection.

APPLICATIONS

Allowing for the most stringent conditions encountered in service, **TALUSIA LS 25** covers the special operational needs of the slow speed 2-stroke engines in compliance with 2015 ECA fuel requirements.

PROPERTIES

This lubricant ensures:

- low alkalinity,
- outstanding cleanliness,
- excellent deposit control using low-ash chemistry.

APPROVALS

TALUSIA LS 25 is approved by MAN Diesel & Turbo, MHI-MME and Wärtsilä.

CHARACTERISTICS

CHARACTERISTICS	METHODS	UNITS	TALUSIA LS 25
S.A.E. Grade			50
Density at 15 °C	ISO 3675	kg/m ³	908
Kinematic viscosity at 100 °C	ISO 3104	mm ² /s	19
Flash Point (COC)	ASTM D 92	°C	> 230
Pour Point	ISO 3016	°C	- 10
BN	ASTM D 2896	mgKOH/g	25

Characteristics of this chart are indicative typical values

HANDLING, HEALTH AND SAFETY

TALUSIA LS 25 consists of highly refined mineral oils with specific additives.

In normal conditions of use, these lubricants present no particular toxic hazard.

All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin.

Prevent any risk of splashing, and keep away from combustible materials.

Store under cover and away from any risk of contamination.

A safety data sheet complying with current legislation is available on [www. quickfds.com](http://www.quickfds.com) or www.lubmarine.com.

The values shown above are typical values at the date of publication. TOTAL Lubmarine reserves the right to change these typical values without prior notice.



TOTAL LUBRIFIANTS
562 avenue du Parc de l'Ile – 92029 Nanterre Cedex
Tel.: 33.1.41.35.59.23 – Fax: 33.1.41.35.20.92
www.lubmarine.com - rm.tma-diagomarplus@total.com