



Product Information:

TERRAIN XL 10W-30 HEAVY DUTY ENGINE OIL

Description:

A high performance heavy duty multigrade engine oil recommended for diesel units fitted to off-highway equipment operating under varying work loads. Terrain XL 10W-30 provides high levels of cleanliness, wear, rust and oxidation protection, together with outstanding soot handling and sludge dispersancy.

Key Features

- Outstanding Soot Handling
- Enhanced Sludge Dispersancy
- High levels of Piston Cleanliness
- Improved Anti-wear protection

Application

Terrain XL 10W-30 can be used in heavy duty diesel engines fitted in off-highway, construction, plant and material handling equipment. This product will cope the demands of EGR (Exhaust Gas Recirculation) and SCR (Selective Catalytic Reduction – Adblue) systems*. This product is also suitable for use in hydraulic systems, power steering, fluid clutches, hydrostatic drives, torque converters, etc, where a 10W-30 grade of this type is recommended.

*Note: Should not be used in engines fitted with a DPF (Diesel Particulate Filter). If a SAE 10W-30 is needed, these engines require Morris Versimax HD7 10W-30.

Performance Level

API CI-4 / SL
ACEA E7 / A3 / B4
Caterpillar ECF-1
Cummins 20076/78
MACK EO-M, EO-M+
Mercedes Benz 228.3
Volvo VDS-3

Physical Characteristics

Relative Density at 15 °C	0.880
Viscosity @ 100 °C	10.52
Viscosity @ 40 °C	71.55
Viscosity Index	137
Flash Point (closed) °C	202
Pour Point °C	-36
TBN, mg/KOH/g	10.0

Figures based on average production values.

Part No.s: TXL005, TXL025, TXL205

(TDS Terrain XL 10W-30 – 120313 Issue 4)

