



Tractran TF-10

Tractor Transmission/Hydraulic Fluid

Product Data

Description

Tractran TF-10 is a high performance fluid blended to meet the complex transmission/hydraulic requirements of modern tractors.

It has the necessary extreme pressure properties and film strength to provide good gear lubrication for manual or power-shift tractor transmissions.

It also provides the anti-wear, anti-foam, anti-oxidation and viscosity characteristics essential for a quality hydraulic fluid.

Tractran TF-10 also provides the optimum frictional characteristics necessary for effective operation of oil-immersed clutches, brakes and fluid couplings.

Benefits

- Superior gear wear protection and frictional characteristics for wet brakes and power-take-off clutches.
- Good water tolerance and excellent filterability necessary for maintaining hydraulics performance.
- Good thermal/oxidative stability and high level of shear stability.
- Excellent anti-corrosion and anti-rust properties.
- One oil reduces inventory and simplifies servicing

Specifications

Tractran TF-10 meets the following approvals:

- M1143, M1145
- Ford M2C 134D
- Volvo VME WB 101
- ZF TE-ML 03E, 05F, 17E

Tractran TF-10 meets the requirements of:

- API GL-4
- Caterpillar TO-2
- M1141, M1135
- Case MS 1207
- JDM J20C

Tractran TF-10 can be used in agricultural equipment where lubricants meetings Case MS 12096, MAT 3505 and MAT 3525 specifications are required.

Tractran TF-10 should **not** be used for top up and should not be mixed with genuine fluids meeting the CASE MS 1209 and MAT 3505 specifications – in these instances, the oil should be completely replaced.



Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health & Safety Recommendations

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products. BP Australia will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local BP office.

Typical characteristics

Test	Method	Unit	Typical Value
Density @ 15°C,	ASTM D4052	kg/L	0.891
Flash Point (COC)	ASTM D92	°C	205
Kinematic Viscosity @ 40°C	ASTM D445	cSt	56.3
Kinematic Viscosity @ 100°C	ASTM D445	cSt	10.0
Viscosity Index	ASTM D97	-	140
Pour Point	ASTM D97	°C	-36

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Tractran TF-10_460446_2013_07 replaces Tractran TF-10_460446_2012_11.docx
22 July 2013:

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence. The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

BP Australia Pty Ltd
ABN 53 004 085 616
Lubes & Fuels Tech Helpline: 1300 139 700
Fax (Australia): 03 9268 4394

www.bp.com