



Transmax Dex III Multivehicle

Automatic Transmission Fluid

No default for Auto Lubes

Castrol Transmax Dex III Multivehicle is designed for use in GM automatic transmissions pre 2005 and Ford automatic transmissions built between 1983 and 1996 where Dexron® (II or III) or Mercon are required. This product is approved for use in Allison heavy duty transmissions against TES 389. It is also approved for use in a wide range of european heavy duty automatic transmissions. It may be used in some power steering units. NB: Do not use where MERCON® V, MERCON® SP or DEXRON® VI is required.

- Multiple manufacturer approvals make it suitable for wide ranging use.
- It is specifically formulated for high thermal stability and resistance to oxidation which protects against the formation of deposits and oil thickening prolonging the life of components and lubricant.
- Optimised friction characteristics provide smooth shifting and efficient power transfer.
- High viscosity index provides a stable viscosity over a wide temperature range for effective protection of transmissions and operation of power steering units

Default

			Transmax Dex III Multivehicle
Density @ 15C, Relative	ASTM D4052	g/ml	0.859
Viscosity, Kinematic 100C	ASTM D445	mm²/s	7.2
Viscosity, Kinematic 40C	ASTM D445	mm²/s	35
Viscosity Index	ASTM D2270	None	175
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	16500
Pour Point	ASTM D97	°C	-46
Flash Point, COC	ASTM D92	°C	216

Allison C4
Allison TES 389
MAN 339 Z1
MAN 339 V1
MB-Approval 236.9
Voith H55.6335.xx
Volvo Transmission Oil 97341
ZF TE-ML 04D, 14A
Meets Mercon®, Dexron® IIIH, Volvo Transmission Oil 97340

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Transmax Dex III Multivehicle
01 Jul 2015
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Ltd, Wakefield House, Pipers Way, Swindon, SN3 1RE, UK

www.castrol.com