

# TRANSWAY AC 10W

## Hydrostatic transmission fluid

### Product description

TRANSWAY AC 10W is a transmission oil for hydraulic transmissions.

### Application areas

TRANSWAY AC 10W is intended for processing machines with a final drive and hydraulic system in combination with wet brakes. TRANSWAY AC 10W is recommended for heavily-loaded processing machines and tractors where a transmission oil as per Caterpillar's TO-4 specification is prescribed.

### Characteristics and advantages

Technology for wear protection and corrosion protection provides a long component lifetime. Friction characteristics according to Caterpillar's TO-4 specification. With TRANSWAY AC 10W, the transmission and brakes are able to work in the correct oil environment, providing an extended oil lifetime and quiet brakes.

### Tests and approvals

Specifications: API GL-4

Fulfills: Allison C-4, CAT TO-4, Eaton I-280-S, Eaton M2950S, Komatsu KES 07.868.1

### Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on [www.statoillubricants.com](http://www.statoillubricants.com) or supplied on request.

### Typical Data

Characteristics	Typical value	Unit	Method
Brookfield viscosity at -35°C	60500	mPas	ASTM D 2983
Density at 15°C	878	kg/m <sup>3</sup>	ISO 12185
Flash point COC	220	°C	ISO 2592
Pour point	-39	°C	ISO 3016
Viscosity at 40°C	43.37	mm <sup>2</sup> / s	ISO 3104
Viscosity at 100°C	6.88	mm <sup>2</sup> / s	ISO 3104
Viscosity index	115	-	ISO 2909

Revision date 03-Sep-2015