

## **Triton® 2000 GEO**

76® Triton 2000 GEO is a high-quality, ashless, dispersant-detergent gas engine oil designed for use in naturally aspirated and moderately turbocharged 2-stroke cycle natural gas engines. Engines operating in this type of service typically are found on crude oil and gas transmission pipelines, electrical power generators, gas compressors, irrigation water pumps and well drilling rigs.

Triton 2000 GEO is formulated with field-proven performance additives to meet the rigorous lubrication demands of modern, fuel-efficient, low-emission gas engines. It provides excellent resistance to oxidation and nitration, protects against ring and liner wear, minimizes the formation of sludge and piston deposits for excellent engine cleanliness, and protects against corrosion. The absence of ash-forming additives results in clean intake ports to help maintain peak engine performance, and also helps extend spark plug life in spark-ignited gas engines.

### ***Applications***

- 2-stroke cycle natural gas engines that are sensitive to port deposits and require an ashless gas engine oil

Triton 2000 GEO is recommended for use in natural gas engines manufactured by:

- Ajax
- Climax
- Colt-Fairbanks Morse
- Cooper-Bessemer
- Dresser Clark
- Dresser Rand (Category I, II)
- Worthington

### ***Features/Benefits***

- Field-proven performance in providing excellent engine cleanliness
- Ashless formulation helps minimize port deposits
- Good dispersancy to protect against sludge and varnish formation
- Excellent resistance to oxidation and nitration
- Protects against scuffing and wear
- Protects against rust and corrosion
- Does not contain any bright stock, which can cause harmful carbon deposits

**Ashless  
Natural Gas  
Engine Oil**

### **CONTACT INFORMATION**

**Phillips66  
Lubricants.com**

U.S. Customer  
Service:  
**1-800-368-7128**

Technical Hotline:  
**1-877-445-9198**

International  
Customer Service:  
**1-832-765-2500**

E-mail address:  
**76lubricants@  
p66.com**

**Triton® 2000 GEO****Typical Properties**

<b>SAE Grade</b>	<b>30</b>	<b>40</b>
Specific Gravity @ 60°F	0.883	0.889
Density, lbs/gal @ 60°F	7.36	7.42
Color, ASTM D1500	3.0	3.5
Flash Point (COC), °C (°F)	211 (412)	270 (518)
Pour Point, °C (°F)	-27 (-17)	-27 (-17)
Viscosity, Kinematic		
cSt @ 40°C	94.7	142
cSt @ 100°C	11.0	14.2
Viscosity Index	101	97
Sulfated Ash, ASTM D874, wt %	<0.01	<0.01
Total Base Number (TBN), ASTM D2896	1.0	1.0
Phosphorus, wt %	0.054	0.054

**Health and Safety Information**

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.