

CEPSA TRONCOIL GAS 40 G

Description



Lubricant oil with a medium ash content.

Formulated with highly-refined, selected paraffinic base oils, with specific, new generation additives that highly efficient in the neutralisation of acids produced during combustion.

Applications

- Especially recommended for normal or supercharged 4-stroke engines that require a medium ash-content oil.

Performance

- Good alkalinity retention. Excellent neutralisation of the acids formed during combustion.
- Notable resistance to foam formation and corrosion.
- Exceptional stability against oxidation and nitration.
- Excellent protection against piston and sleeve wear.
- Maximum valve and seat protection.
- Low tendency to form carbon deposits and residues.

Specifications

- API CD
- The set of additives applied in the formulation has been satisfactorily evaluated by the following manufacturers: CATERPILLAR, AJAX, DRESSER-RAND (CLARK), WAUKESHA, COOPER-BESSEMER, SUPERIOR.

Typical Characteristics

CHARACTERISTICS	ASTM STANDARD	CEPSA TRONCOIL GAS
SAE GRADE		40 G
Density at 15 °C, g/cc	D-4052	0,897
Flash Point, COC, °C, min	D-92	>220
Pour Point, °C	D-97	-18
Viscosity at 100 °C, cSt	D-445	13,88
Viscosity at 40 °C, cSt	D-445	135,6
Viscosity Index, min.	D-2270	99
Base Number, mg KOH/gm	D-2896	8,9
Sulphated ashes, % weight	D-874	0,88

Health & Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes. These values may be modified without any prior warning.