



NESTE TURBO LXE 10W-30

Part synthetic diesel engine oil

SAE 10W-30

Neste Turbo LXE is developed for heavy-duty truck professionals. It is especially suitable for heavy-duty vehicles and construction machines engines with extended oil change intervals and can be also use in passenger cars and vans with diesel engines.

Neste Turbo LXE exceeds the requirements of the new ACEA E7 and API CI-4 standards. It meets also the requirements of low emission Euro II and III engines. Oil guarantees good engine cleanliness, a high degree of protection against wear and low oil consumption.

Neste Turbo LXE 10W-30 can be used as wintertime oil if Neste Turbo LXE 15W-40 is used in summer time.

TYPICAL CHARACTERISTICS	10W-30
Densitykg/m ³ 15°C	874
Flash Point°C (COC)	228
Pour Point°C	-42
Viscosity Index	145
ViscositycSt/ 40 °C	77
ViscositycSt/ 100 °C	11,7
ViscositycP/ °C	6700
Total Base Number, ASTM D2896	10,5
Sulphated Ash, %-w	1,4

API CI-4/SL, CH-4, CG-4, CF-4

ACEA E7, E5, E3

MB 228.3

Volvo VDS-3, Volvo VDS-2

MAN M 3275, Mack EO-N, EO-M Plus, Cummins CES 20,071/-2/-6/-7/-8

Renault RVI RLD, RLD-2

Global DHD-1

Caterpillar ECF-2, ECF-1-a

MTU Type 2

Deutz DQC III-10

Neste Markkinointi Oy

PL 95, 00095 NESTE OIL

www.neste.fi

Technical service

+358 200 11311

Updated 27.8.2014

Print

Close