



NESTE TURBO SUPER 5W-30

Fully Synthetic Ultra High Performance Diesel Engine Oil

ACEA E7/E4,
MB 228.5, MAN 3277, MTU Type 3
Volvo VDS-3, Volvo VDS-2, RVI RXD
Mack EO-M+, Cummins CES 20,071/-2/-6/-7
Scania LDF

Neste Turbo Super 5W-30 is fully synthetic ultra high performance diesel engine oil for high performance diesel engines and long oil drain intervals.

Neste Turbo Super 5W-30 exceeds the requirements of ACEA E7 and ACEA E4 standards and meets also the requirements of low emission engines Euro II, Euro III, Euro IV and engines with EGR. It meets the top performance requirements of European and North American engine manufacturers. Oil guarantees good engine cleanliness, a high degree of protection against wear and low oil consumption. In field and bench tests run in Finland Neste Turbo Super 5W-30 has proven a fuel saving properties compared to traditional diesel engine oils.

Benefits:

- * Excellent cold properties
- * Fuel saving properties
- * Superb protection against bore polishing
- * Provides excellent engine cleanliness
- * Avoids the formation of sludge deposits caused by combustion soot
- * Protects against cylinder and cam wear
- * Offers prolonged oil drain intervals
- * Reduces maintenance costs

TYPICAL CHARACTERISTICS

Densitykg/m ³ 15°C	860
Flash Point°C (COC)	229
Pour Point°C	-54
Viscosity Index	165
ViscositycSt/ 40 °C	72
ViscositycSt/ 100 °C	12
ViscositycP/ °C	6100
TBN mgKOH/g	17,2

Neste Markkinointi Oy
PL 95, 00095 NESTE OIL
www.neste.fi

Technical service
+358 200 11311
Updated 24.10.2014

[Print](#)[Close](#)