

DIESEL MOTOR OIL

TURBO-MOTOR SUPER 15W-40

PRODUCT DESCRIPTION

TURBOMOTOR SUPER 15W-40 is a high performance diesel engine oil that provides proven protection of diesel engines operating on and off-highway severe service applications.

TURBOMOTOR SUPER 15W-40 is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

- | | |
|--------------------------------------|---|
| ■ Thermal and oxidation stability : | Control sludge build-up and deposit |
| ■ TBN reserve : | Deposit control |
| ■ Stay-in-grade shear stability : | Reduced oil consumption and wear protection |
| ■ Excellent detergency/dispersancy : | Cleaner engines and longer engine life |
| ■ Component compatibility : | Longer gasket and seal life |
| ■ | |

Applications:

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese, and American manufacturers.
- On-highway light and heavy-duty trucking.
- Off-highway industries including construction, mining, quarrying, and agriculture.

Specifications

VOLVO VDS-2	MAN 271	ACEA A3, B4, B3, , E3
MACK EO-L	MB 228.3	API CG-4/CF-4/CF/SJ
	ALLISON C- 4	
	MB 229.1	VW 501/505

Typical properties

	TURBO MOTOR SUPER 15W40
Density@15C kg/l	0.890
Viscosity ASTM D 445 cst@40c	115
Viscosity ASTM D 445 cst@100c	15.0
Viscosity Index ASTM D 874	130
Flash Point/,C/,ASTM D 92	210
Pour Point,C,ASTM D 97	-15 ⁰ c
Total Base #mg KOH/g	11.0

Delek Lubricants

P.O.B 31 Lod 71100 ISRAEL. Tel: 972-8-9270820, Fax: 972-8-8247072
www.dekleklubes.com