



Sasol Universal Transmission Oil 68

MULTIPURPOSE GEAR & TRANSMISSION OIL, GRADE 68

(SAE 80W)

Description

Sasol Universal Transmission Oil 68 is a multipurpose gear and transmission oil with a viscosity equivalent to that of a SAE 20W engine oil.

Application

Sasol Universal Transmission Oil 68 is intended for:

- tractor transmissions and hydraulic systems
- differentials equipped with wet brakes
- drive train systems
- torque converters
- gear units of certain commercial and construction vehicles

Features and Benefits

Sasol Universal Transmission Oil 68 can serve as a replacement for all oils, other than engine oil, used in agricultural tractors. This type of oil is sometimes also referred to as Universal Tractor Transmission Oil or UTTO.

It can be used in wet brake and many drive train applications and is specially formulated for good:

- chatter suppression
- low temperature performance
- anti-foam properties

Product Specifications

Allison C-3 & C-4

API GL-4

Caterpillar TO-2

Ford M2C134 - A/B/C/D; M2C86 – B/C

New Holland: FNHA-2-C-210.00

John Deere J20C

Massey Ferguson M1110 – M1145

ZF (Tractors) TE-ML-03E, -05F, -06

JI Case MS 1204 to MS 1210 – B6

Typical Characteristics

Property	Units	Typical	ASTM	IP
Viscosity			D445	71
@ 100°C	mm ² /s	9.7		
@ 40°C	mm ² /s	65		



Viscosity Index		157	D2270	226
Pour Point	°C	-36	D97	15
Flash Point (COC)	°C	240	D92	36
Density @ 20°C	kg/m ³	889	D4052	365

Storage and Handling

Use PVC, nitrile or other oil resistant gloves and protective clothing to prevent skin contact. Where eye contact is a potential hazard, goggles should be worn.

Avoid temperatures above 80°C and strong oxidizing agents.

Ambient temperatures and atmospheric pressures normally encountered within buildings or roofed-over outdoor storage areas are acceptable. Avoid entering areas where mists or vapours have built up as a result of abnormal temperatures or pressures without the proper breathing equipment and protective clothing.

Pack Information

<u>Product Code</u>	<u>Pack Size</u>
300192	20 L
300193	210 L
300194	Bulk