



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE UTF

LUBRIPLATE UTF is a high quality, specially designed lubricant containing anti-rust, anti-foam and oxidation inhibitors; plus other additives necessary for the wide range of applications recommended by various tractor manufacturers. The product is an “all-seasonal” type of oil that resists thickening in cold weather and thinning in the heat of the summer. It is compounded with detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition; and provides excellent protection against seal and pump deterioration. Operators, especially farmers, will appreciate the multipurpose application for transmissions, final drives, and hydraulic systems of tractors thereby eliminating the need for additional oil products.

Benefits:

- Excellent gear, bearing and pump wear protection
- Multi-functional fluid
- Oxidation and thermal stability for long life
- Excellent rust and corrosion protection
- Reduces brake chatter
- Compatibility with oil seal materials used in transmission and hydraulic systems

LUBRIPLATE UTF is recommended for use in equipment made by:

Allison - Hydraulic Trans Fluid; GMC, Type C, C-1, C-2, C-3, C-4

Allis-Chalmers - #272843, Part #924282 (Power Fluid No. 821), Part #246634

Caterpillar - TO-2

Clark Transmissions

Duetz-Allis - 272843 (Power Fluid 821XL)

J. I. Case - Hi-Lo CH Fluid JIC 145, Case-O-Matic Type A, JIC 143, JIC 144, JIC-C-185 (TFD), MS-1205 (TFD-II), MS-1206 (Powerguard PTF), MS-1207 (Hy-Trans-Plus), MS-120 1, MS-1209 (Hy-Tran ULTRA)

Ford New Holland - M-2C41 Selecto-Speed Fluid, ESN M-2-C41A, M-2C41-B, M-4864A, M-2C65A, M-2C77A, M-4864B, M-2C65B, M-2C78A, M-2C86A, M-2C134B, M-2C134D, FNHA-2-C-200 & 201

(Continued)

LUBRIPLATE UTF is recommended for use in equipment made by:

Fiat Hesston - AF-87

International Harvester - Hy-trans Fluid, (B-5, B-6, B-7)

John Deere - Fluid Type 303 (J-14C), Part #AR-284254, Part #AR-269444, J-14B, J-20A, J-20B (Hy-Guard), J-20C, Quatrol Requirements, J21A, J20D

Kubota - UDT Fluid

Landini

Massey Ferguson - M-1103A, M-1103B, M-1110, M-129A, M1135, Permatron III, M-1141

Oliver - Where additive Part #102082A is mixed with 10W, 5W20, 10W30 oil; in 1 part to 16 parts oil, Type 55 and Renk 874 A/B transmission

White - Universal Fluid

Stieger - Hydraulic Trans Fluid, Gear, Hydraulic and Wet Brake Oil

Sundstrand - Pumps

Versatile - Specs 23M or 24M

White Farm - Hydraulic Oil Type 55 Fluid, White Universal Fluid, White Farm Q-1760, Q-17668, White UTHF, Q-1826

Typical Characteristics:

SAE Grade	10W20
API Gravity	28.4
Viscosity @ 40°C, cSt	58.9
Viscosity @ 100°C, cSt	8.7
Viscosity Index	133
Brookfield Vis @ -18°C, cP	4,000 max
Brookfield Vis @ -34°C, cP	70,000 max
Pour Point, °F	-35

LUBRIPLATE UTF is available as follows:

<u>Packaging Available</u>	<u>Part No.</u>
Case, 4/1 Gallon Jugs	L0873-057
5 Gallon Pail	L0873-060
16 Gallon Drum	L0873-061
55 Gallon Drum	L0873-062