



## **Vanellus C Mono 30**

Automotive Crankcase Lubricant

## **Product Data**

### **Description**

**Vanellus C Mono 30** engine oil has been designed for use in naturally aspirated diesel engines where API Service Classification "CC" lubricants have been specified.

It has been formulated using high quality base oils, together with a carefully balanced chemical additive system to provide good engine protection. It is also suitable for use in older petrol engines.

### **Benefits**

- High levels of cleanliness and wear protection in all engines requiring API CC/SE performance.
- Good high temperature performance controls the formation of lacquers and deposits.
- Provides protection against low temperature sludge formation.
- Cost-effective alternative in many naturally aspirated diesel engines.

### **Specifications**

**Vanellus C Mono 30** exceeds the performance requirements of API Engine Service Classification CC/SE.



## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

## Health & Safety Recommendations

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products. BP Australia will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local BP office.

## Typical characteristics

Test	Method	Unit	Typical Value
Density @ 15°C,	ASTM D1298	kg/L	0.895
Flash Point (PMC)	ASTM D93	°C	230
Kinematic Viscosity @ 40°C	ASTM D445	cSt	107
Kinematic Viscosity @ 100°C	ASTM D445	cSt	11.8
Viscosity Index	ASTM D2270	-	99
Pour Point	ASTM D97	°C	-21
Sulphated Ash	ASTM D874	% wt	0.54

*The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.*

Vanellus\_C\_Mono\_30\_200709.doc

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence. The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

**BP Australia Pty Ltd**  
**ABN 53 004 085 616**  
**Lubes & Fuels Tech Helpline: 1300 139 700**  
**Fax (Australia): 03 9268 4394**

[www.bp.com](http://www.bp.com)