

Sasol White Oil 15 & 68 WHITE OIL, MEDICINAL, GRADES 15 & 68

Description

Sasol White Oil 15 & 68 are tasteless, odourless, water-white oils, specially refined and treated to reduce their polycyclic aromatic content to vanishingly low levels.

Application

Sasol White Oil 15 & 68 can be used for all applications where pharmaceutical or technical grade white oils are required.

Features and Benefits

Sasol White Oil 15 & 68 can also be used as:

- plasticisers and/or extenders for certain polymers and elastomers
- lubricants for food processing machinery
- base oils in the manufacture of explosives
- lubricants for submersible pumps

Although more highly refined than required for technical white oils, Sasol White Oil 15 & 68 may be used as lubricants in oil-flooded sulphur dioxide refrigerant compressors.

Product Specifications

British Pharmacopoeia Liquid Paraffin German Pharmacopoeia DAB 9 Paraffin, Liquid Government Gazette 1856 & 5406 (R230) Sasol S226 & S170 U.S. Federal Drugs Administration CFR 172.878 & CFR 178.3620 (A)

U.S. Pharmacopoeia Light Mineral Oil

Typical Characterist	ics				
Property	Units	15	68	ASTM	IP
Viscosity				D445	71
@ 100°C	mm²/s	2,8	9		
@ 40°C	mm²/s	14,5	70		
Colour (Saybolt)	-	+30	+30	D156	-
Pour Point	°C	-18	-6	D97	15
Flash Point (COC)	°C	172	235	D92	36
Density @ 20°C	kg/m ³	853	866	D4052	365



Storage and Handling

Use PVC, nitrile or other oil resistant gloves and protective clothing to prevent skin contact. Where eye contact is a potential hazard, goggles should be worn.

Avoid temperatures above 80°C and strong oxidizing agents.

Ambient temperatures and atmospheric pressures normally encountered within buildings or roofed-over outdoor storage areas are acceptable. Avoid entering areas where mists or vapours have built up as a result of abnormal temperatures or pressures without the proper breathing equipment and protective clothing.

Pack Informati	tion		
Grades	Product Code	Pack Size	
15		210 L	
68		210 L	
		20 L	