



Wool Processing Oil

Wool Processing Oil is a high-quality, low-viscosity mineral oil developed for use as a wool processing oil. It improves cohesion of the wool fibers and helps protect them during processing and spinning the wool into yarn. It also helps reduce static during processing.

Wool Processing Oil has very light color and is nonstaining. It is inhibited against oxidation to maintain color stability.

Applications

- Wool processing

Features/Benefits

- Very light color
- Nonstaining
- Good color stability

**Light Mineral Oil
For Processing &
Spinning Wool**

CONTACT INFORMATION

**Phillips66
Lubricants.com**

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
**lubricants@
p66.com**



Wool Processing Oil

Typical Properties

ISO Grade	22
Specific Gravity @ 60°F	0.853
Density, lbs/gal @ 60°F	7.10
Color, ASTM D1500	L 0.5
Flash Point (COC), °C (°F)	209 (408)
Pour Point, °C (°F)	-15 (5)
Viscosity,	
cSt @ 40°C	20.3
cSt @ 100°C	4.1
SUS @ 100°F	107
SUS @ 210°F	40.1
Viscosity Index	101

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2015 Phillips 66 Company. Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.